

CHASSIS

Room slideouts	74
Caravan movers	75
Steps and jacks	77
Jockey wheels and accessories	78

BRIDGE
LOAD
LIMIT
25t
GROSS





ROOM SLIDEOUTS

POWER GEAR - ROOM SLIDEOUTS

042610 DUAL RAIL SLIDEOUT KIT

The Power Gear Room Slide Out System in your RV, motorhome or horse-truck is designed to give you years of trouble-free operation and reflects the latest state of the art technology. It is a rack and pinion design operated by a 12V high powered electric motor.

FEATURES:

- Inner and outer rail assemblies to support the room weight
- 12V motor for on-board operation
- Manual override in event of an emergency
- Load sensing control unit

SPECIFICATIONS:

- Rail can support 545kg at 90cm extension
- Maximum distance between rails is 380cm. Maximum room with this width is 760cm



TRAIL-A-MATE HYDRAULIC JOCKEY WHEEL AND JACK

043492

A hydraulic jockey wheel that converts in to a jack when you need it. You simply swap the wheel for a solid base plate. The key features of the Trail-A-Mate are as follows:

- Capability - WLL 1,000kg / ATM 2,900kg
- Versatility - Easily converts from a jockey wheel to a jack
- Ease of Use - Being hydraulic it takes very little effort to operate
- Safety - Fully complies with the Australian mandatory safety standards (2693:2007)

It has many applications and uses such as caravanning, horse floats, trailers, food vans, motorhomes.

FEATURES:

- For stress free raising and lowering of caravans, boats and trailers
- Safety nonslip lugs built in
- No need to climb under the vehicle to jack it up
- Suitable for most jockey wheel brackets
- Both a jack and jockey wheel
- Trail-A-Mate - safe working load of 1000kg when base is fitted
- Trail-A-Mate II - safe working load of 1500kg when base is fitted



TRAILAMATE SPARE PARTS

040981 JACK ONLY MARKII LIFTING CAP. 1500KG. NO WHEEL. BRACKET SOLD SEPARATELY.

042460 TRAILAMATE CLAMP 60MM



TRAILER VALET MOVER
042965

Manual mover designed for trailers up to 2,200kg with a ball weight of up to 220kg. Perfect for small caravans, campers and car trailers. Very simple to use.

FEATURES:

- Attaches to your A-frame and can replace your jockey wheel
- Patented drive system with high and low drive gears (select high or low gear depending on your terrain)
- Brake is incorporated in the system for safety
- Unit can be rotated out of the way on the mount for travel or removed completely
- Spare mounting plates are available to enable you to move the Trailer Valet from one vehicle to another easily

SPECIFICATIONS:

- Weight: 20.5kg
- High quality steel with powder-coated hammer finish
- 2 x 9" pneumatic tyres

TRAILER VALET XL MOVER
043705

The Trailer Valet XL is the toughest and most compact trailer dolly. Sharing the same great features as its little brother, but with a few upgrades. The XL moves most trailers up to 4,500kg just using a crank handle or an 18V drill. It features dual, 9" tyres that can handle a ball weight of up to 400kg and positraction technology for making tight turns. The automatic brake engages when the handle is released for superior safety, making it ideal for large caravans, boats, construction and farm equipment, horse floats and flat bed trailers.

FEATURES:

- Handles most trailers weighing up to 4,500kg (450kg tongue weight)
- Patented ball attachment mechanism for quick attachment and greater manoeuvrability
- High strength pneumatic tyres that can withstand 225kg of pressure per tyre
- A greater gear reduction to make cranking even easier
- High quality steel with powdercoat hammer finish
- Brass bearings
- Drill attachment that enables the user to attach most 18V cordless drills
- Automatic safety brake
- One year manufacturer's warranty
- Positraction for maximum traction and ease of handling

SPECIFICATIONS:

- Tow ball coupling ball size: 50mm
- Weight: 23.5kg



TRAILER VALET BRAKE CAP HANDLE
042969



TRAILER VALET DRILL ATTACHMENT
043706



TRAILER VALET TYRE AND TUBE 2X9"
042967



TRAILER VALET CRANK HANDLE
042968

CARAVAN MOVERS



CARAVAN MOVER ELITE® 2 043321

- Economical and effective solution for manoeuvring your caravan
- Aluminium rollers that are friendly to tyres
- Optimum compact design, reasonable ground clearance, suitable for almost any light duty single axle chassis
- Corrosion-protected by e-coating and powder coating
- Easy winding action to engage or disengage the roller.
- The powerful motor will not allow the RV to roll while being manoeuvred on a gradient (Do not use the system as a brake. Always disengage rollers when not in use)
- Caravan/trailer stops immediately and automatically if it is out of range of the remote control or there is malfunction
- Not submersible

MODEL	ELITE® 2 EM303
PART NUMBER	043321
OPERATIONAL VOLTAGE	12V DC
AVERAGE CURRENT CONSUMPTION	20 AMPS
MAXIMUM CURRENT CONSUMPTION	100 AMPS
REMOTE CONTROL TRANSMITTING FREQUENCY	868 MHZ
SPEED	90MM / SEC.
WEIGHT	37KG APPROX.
SAFE WORKING LOAD (SWL)	1,800KG (2 MOTORS) – UP TO 1,500KG ON AN 18% GRADIENT 2,500KG (4 MOTORS) – UP TO 1,800KG ON AN 18% GRADIENT
MINIMUM WIDTH (CARAVAN/TRAILER)	1800MM
MAXIMUM WIDTH (CARAVAN/TRAILER)	2500MM
MAXIMUM TYRE WIDTH	205MM

CARAVAN MOVER ELITE® PRO 2 043322

- Accurate and durable gearing
- Aluminium rollers that are friendly to tyres
- Simply by pressing the button on remote control handset the rollers will properly engage or disengage on the tyres
- Manoeuvre your caravan effortlessly with soft stop and start
- The powerful motor will not allow the RV to roll while being manoeuvred on a gradient (Do not use the system as a brake. Always disengage rollers when not in use)
- Caravan/trailer stops immediately and automatically if it is out of range of the remote control or there is malfunction
- If you forget to disengage the rollers, an emergency function will wind them back if it is connected to a tow vehicle.
- Not submersible

MODEL	ELITE® PRO 2 EM305
PART NUMBER	043322
OPERATIONAL VOLTAGE	12V DC
AVERAGE CURRENT CONSUMPTION	30 AMPS
MAXIMUM CURRENT CONSUMPTION	120 AMPS
REMOTE CONTROL TRANSMITTING FREQUENCY	868 MHZ
SPEED	110MM / SEC.
WEIGHT	33KG APPROX.
SAFE WORKING LOAD (SWL)	2,000KG (2 MOTORS) – UP TO 1,750KG ON AN 18% GRADIENT 3,000KG (4 MOTORS) – UP TO 2,350KG ON AN 18% GRADIENT
MINIMUM WIDTH (CARAVAN/TRAILER)	1800MM
MAXIMUM WIDTH (CARAVAN/TRAILER)	2500MM
MAXIMUM TYRE WIDTH	205MM

CAMEC CARAVAN MOVER SPARE PARTS

042624	EM303 REMOTE HANDSET SERIES 1 FOR CAMEC ELITE MOVER	043497	MOVER MOUNTING PLATES SET OF 2 FOR ELITE AND PRO WITH BOLTS	043683	EM303/305 MAIN SWITCH WITH KEY & WALL MOUNTING HOUSING
042625	EM303 CONTROL UNIT SERIES 1 FOR CAMEC ELITE MOVER	043498	MAINFRAME COVER ELITE	043687	EM303 A MOTOR BRACKET
042628	ISOLATION KEY FOR CAMEC ELITE AND ELITE PRO MOVER	043499	MAINFRAME COVER ELITE PRO	043688	EM303 B MOTOR BRACKET
042632	MOTOR RUBBER COVER IN PAIR FOR CAMEC ELITE MOVER	043663	EM303/305 WALL HOLDER FOR REMOTE HANDSET	043689	EM305 A MOTOR BRACKET
042633	EM305 REMOTE HANDSET SERIES 1 FOR CAMEC ELITE PRO MOVER	043674	EM303 REMOTE HANDSET SERIES 2	043690	EM305 B MOTOR BRACKET
042634	EM305 CONTROL UNIT SERIES 1 FOR CAMEC ELITE PRO MOVER	043675	EM305 REMOTE HANDSET SERIES 2		
		043676	EM303 CONTROL BOX SERIES 2		
		043677	EM305 CONTROL BOX SERIES 2		
		043679	EM303/305 EMERGENCY KEY		



ELECTRIC STEP SINGLE 12V
001227



RV STEP TWIN LONG 65CM
002600
Black 24".



LEG PADS BIG FOOT SET 4 ALKO
006486



ELECTRIC STEP DOUBLE 12V
001228



RV STEP TRIPLE LONG 66CM
002601
Black 24".



DYMWOOD 18" ADJUSTABLE FRONT LEG SLOT
000282



STEP SINGLE MANUAL 0721001/A
001362



RV STEP SINGLE SHORT 51CM
002602
Black 20".



ADJUSTABLE LEG HANDLE ARTWELL
000284
Slotted handle.
565mm overall size



RV STEP SINGLE LONG 63CM
002599
Black 24".



RV STEP TWIN SHORT 51CM
002603
Black 20".



HEX CRANK HANDLE - CAMEC
043248 670MM LONG
043249 780MM LONG

ELECTRIC STEPS SPARE PARTS

- 001189 MOTOR GEAR W/SHAFT T/S NUOVA
- 001195 MOTOR COMPLETE- ELECTRIC SINGLE STEP 12V
- 001196 TENSION SPRINGS PAIR - STEP
- 001505 SWITCH & LOOM T/S NUOVA SINGLE STEP
- 001509 SWITCH ONLY T/S NUOVA MAPA STEPS

- 001881 MICRO SWITCH ONLY FOR NUOVA ELECTRIC STEP
- 002592 STEP ELECTRIC 28SER MOTOR+SCREWS
- 034280 QUICK RELEASE LEG ADJUSTABLE 415MM LARGE ALUMINIUM FOOT,